

# The **mdframed** package

Examples for **framemethod=PS Tricks**

Marco Daniel

v1.6b

2012/06/02

In this document I collect various examples for **framemethod=PS Tricks**. Some presented examples are more or less exorbitant.

## Contents

<b>1 Loading</b>	<b>1</b>	Example 2 – hidden line + frame title	2
		Example 3 – Dash Lines . . . . .	3
<b>2 Examples</b>	<b>1</b>	Example 4 – Double Lines . . . . .	3
Example 1 – very simple . . . . .	2	Example 5 – Shadow frame . . . . .	3

## 1 Loading

In the preamble only the package **mdframed** with the option **framemethod=PS Tricks** is loaded. All other modifications will be done by **\mdfdefinestyle** or **\mdfsetup**.

### Note

Every **\global** inside the examples is necessary to work with the package **showexpl**. X

## 2 Examples

All examples have the following settings:

```
\mdfsetup{skipabove=\topskip,skipbelow=\topskip}
\newrobustcmd\ExampleText{%
An \textit{inhomogeneous linear} differential equation
has the form
\begin{align}
L[v] = f,
\end{align}
where $L$ is a linear differential operator, $v$ is
the dependent variable, and $f$ is a given non-zero
function of the independent variables alone.
}
```

**Example 1 – very simple**

```
\global\mdfdefinestyle{exampledefault}{%
  \linecolor=red,\middlelinewidth=3pt,%
  \leftmargin=1cm,\rightmargin=1cm
}
\begin{mdframed}[style=exampledefault,\roundcorner=5]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (1)$$

where  $L$  is a linear differential operator,  $v$  is the dependent variable, and  $f$  is a given non-zero function of the independent variables alone.

**Example 2 – hidden line + frame title**

```
\global\mdfapptodefinestyle{exampledefault}{%
  \topline=false,\rightline=false,\bottomline=false,
  \frametitle=rule=true,\innertopmargin=6pt,
  \outerlinewidth=6pt,\outerlinecolor=blue,
  \pstricksappsetting={\addtopsstyle{mdfouterlinestyle}{linestyle=dashed}},
  \innerlinecolor=yellow,\innerlinewidth=5pt}%
\begin{mdframed}[style=exampledefault,\frametitle={Inhomogeneous linear}]
\ExampleText
\end{mdframed}
```

**Inhomogeneous linear**

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \quad (2)$$

where  $L$  is a linear differential operator,  $v$  is the dependent variable, and  $f$  is a given non-zero function of the independent variables alone.

**Example 3 – Dash Lines**

```
\global\mdfdefinestyle{exampledefault}{%
  pstrickssetting={linestyle=dashed,},linecolor=red,linewidth=5pt}
\begin{mdframed}[style=exampledefault,]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \tag{3}$$

where  $L$  is a linear differential operator,  $v$  is the dependent variable, and  $f$  is a given non-zero function of the independent variables alone.

**Example 4 – Double Lines**

```
\global\mdfdefinestyle{exampledefault}{%
  pstrickssetting={doubleline=true,doublesep=6pt},
  linecolor=red,linewidth=5pt,middlelinewidth=4pt}
\begin{mdframed}[style=exampledefault,]
\ExampleText
\end{mdframed}
```

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \tag{4}$$

where  $L$  is a linear differential operator,  $v$  is the dependent variable, and  $f$  is a given non-zero function of the independent variables alone.

**Example 5 – Shadow frame**

```

\newmdenv[shadow=true,
           shadowsize=11pt,
           linewidth=8pt,
           frametitle=rule=true,
           roundcorner=10pt,
           ]{myshadowbox}
\begin{myshadowbox}[frametitle={Inhomogeneous linear}]
\ExampleText
\end{myshadowbox}

```

### Inhomogeneous linear

An *inhomogeneous linear* differential equation has the form

$$L[v] = f, \tag{5}$$

where  $L$  is a linear differential operator,  $v$  is the dependent variable, and  $f$  is a given non-zero function of the independent variables alone.